

CD4029BM/CD4029BC Presettable Binary/Decade Up/Down Counter

General Description

The CD4029BM/CD4029BC is a presettable up/down counter which counts in either binary or decade mode depending on the voltage level applied at binary/decade input. When binary/decade is at logical "1", the counter counts in binary, otherwise it counts in decade. Similarly, the counter counts up when the up/down input is at logical "1" and vice versa.

A logical "1" preset enable signal allows information at the "jam" inputs to preset the counter to any state asynchronously with the clock. The counter is advanced one count at the positive-going edge of the clock if the carry in and preset enable inputs are at logical "0". Advancement is inhibited when either or both of these two inputs is at logical "1". The carry out signal is normally at logical "1" state and goes to logical "0" state when the counter reaches its maximum


count in the "up" mode or the minimum count in the "down" mode provided the carry input is at logical "0" state.

All inputs are protected against static discharge by diode clamps to both V_{DD} and V_{SS} .

Features

- Wide supply voltage range 3V to 15V
- High noise immunity 0.45 V_{DD} (typ.)
- Low power fan out of 2 driving 74L or 1 driving 74LS
- TTL compatibility
- Parallel jam inputs
- Binary or BCD decade up/down counting

Logic Diagram



TL/F/5960-1

CD4029BM/CD4029BC Presettable Binary/Decade Up/Down Counter

Absolute Maximum Ratings

(Notes 1 and 2)

If Military/Aerospace specified devices are required, please contact the National Semiconductor Sales Office/Distributors for availability and specifications.

| | |
|-------------------------------------|----------------------------------|
| DC Supply Voltage (V_{DD}) | -0.5V to +18 V_{DC} |
| Input Voltage (V_{IN}) | -0.5V to V_{DD} + 0.5 V_{DC} |
| Storage Temperature Range (T_S) | -65°C to +150°C |
| Power Dissipation (P_D) | |
| Dual-In-Line | 700 mW |
| Small Outline | 500 mW |
| Lead Temperature (T_L) | |
| (Soldering, 10 seconds) | 260°C |

Recommended Operating Conditions

(Note 2)

| | |
|---------------------------------------|-------------------------|
| DC Supply Voltage (V_{DD}) | 3V to 15 V_{DC} |
| Input Voltage (V_{IN}) | 0V to V_{DD} V_{DC} |
| Operating Temperature Range (T_A) | |
| CD4029BM | -55°C to +125°C |
| CD4029BC | -40°C to +85°C |

DC Electrical Characteristics CD4029BM (Note 2)

| Symbol | Parameter | Conditions | -55°C | | +25°C | | | +125°C | | Units |
|----------|------------------------------------|-------------------------------------|-------|------|-------|------------|------|--------|------|---------|
| | | | Min | Max | Min | Typ | Max | Min | Max | |
| I_{DD} | Quiescent Device Current | $V_{DD} = 5V$ | | 5 | | | 5 | 5 | 150 | μA |
| | | $V_{DD} = 10V$ | | 10 | | | 10 | | 300 | μA |
| | | $V_{DD} = 15V$ | | 20 | | | 20 | | 600 | μA |
| V_{OL} | Low Level Output Voltage | $ I_O < 1 \mu A$ | | | | | | | | |
| | | $V_{DD} = 5V$ | | 0.05 | | 0 | 0.05 | | 0.05 | V |
| | | $V_{DD} = 10V$ | | 0.05 | | 0 | 0.05 | | 0.05 | V |
| V_{OH} | High Level Output Voltage | $ I_O < 1 \mu A$ | | | | | | | | |
| | | $V_{DD} = 5V$ | 4.95 | | 4.95 | 5 | | 4.95 | | V |
| | | $V_{DD} = 10V$ | 9.95 | | 9.95 | 10 | | 9.95 | | V |
| V_{IL} | Low Level Input Voltage | $V_{DD} = 5V, V_O = 0.5V$ or 4.5V | | 1.5 | | | 1.5 | | 1.5 | V |
| | | $V_{DD} = 10V, V_O = 1V$ or 9V | | 3.0 | | | 3.0 | | 3.0 | V |
| | | $V_{DD} = 15V, V_O = 1.5V$ or 13.5V | | 4.0 | | | 4.0 | | 4.0 | V |
| V_{IH} | High Level Input Voltage | $V_{DD} = 5V, V_O = 0.5V$ or 4.5V | 3.5 | | 3.5 | | | 3.5 | | V |
| | | $V_{DD} = 10V, V_O = 1V$ or 9V | 7.0 | | 7.0 | | | 7.0 | | V |
| | | $V_{DD} = 15V, V_O = 1.5V$ or 13.5V | 11.0 | | 11.0 | | | 11.0 | | V |
| I_{OL} | Low Level Output Current (Note 3) | $V_{DD} = 5V, V_O = 0.4V$ | 0.64 | | 0.51 | 0.88 | | 0.36 | | mA |
| | | $V_{DD} = 10V, V_O = 0.5V$ | 1.6 | | 1.3 | 2.25 | | 0.9 | | mA |
| | | $V_{DD} = 15V, V_O = 1.5V$ | 4.2 | | 3.4 | 8.8 | | 2.4 | | mA |
| I_{OH} | High Level Output Current (Note 3) | $V_{DD} = 5V, V_O = 4.6V$ | -0.64 | | -0.51 | -0.88 | | -0.36 | | mA |
| | | $V_{DD} = 10V, V_O = 9.5V$ | -1.6 | | -1.3 | -2.25 | | -0.9 | | mA |
| | | $V_{DD} = 15V, V_O = 13.5V$ | -4.2 | | -3.4 | -8.8 | | -2.4 | | mA |
| I_{IN} | Input Current | $V_{DD} = 15V, V_{IN} = 0V$ | | -0.1 | | -10^{-5} | -0.1 | | -1.0 | μA |
| | | $V_{DD} = 15V, V_{IN} = 15V$ | | 0.1 | | 10^{-5} | 0.1 | | 1.0 | μA |

DC Electrical Characteristics CD4029BC (Note 2)

| Symbol | Parameter | Conditions | -40°C | | +25°C | | | +85°C | | Units |
|----------|---------------------------|-------------------|-------|------|-------|-----|------|-------|------|---------|
| | | | Min | Max | Min | Typ | Max | Min | Max | |
| I_{DD} | Quiescent Device Current | $V_{DD} = 5V$ | | 20 | | | 20 | | 150 | μA |
| | | $V_{DD} = 10V$ | | 40 | | | 40 | | 300 | μA |
| | | $V_{DD} = 15V$ | | 80 | | | 80 | | 600 | μA |
| V_{OL} | Low Level Output Voltage | $ I_O < 1 \mu A$ | | | | | | | | |
| | | $V_{DD} = 5V$ | | 0.05 | | 0 | 0.05 | | 0.05 | V |
| | | $V_{DD} = 10V$ | | 0.05 | | 0 | 0.05 | | 0.05 | V |
| V_{OH} | High Level Output Voltage | $ I_O < 1 \mu A$ | | | | | | | | |
| | | $V_{DD} = 5V$ | 4.95 | | 4.95 | 5 | | 4.95 | | V |
| | | $V_{DD} = 10V$ | 9.95 | | 9.95 | 10 | | 9.95 | | V |
| V_{OH} | High Level Output Voltage | $V_{DD} = 15V$ | 14.95 | | 14.95 | 15 | | 14.95 | | V |

Note 1: "Absolute Maximum Ratings" are those values beyond which the safety of the device cannot be guaranteed. Except for "Operating Temperature Range" they are not meant to imply that the devices should be operated at these limits. The table of "Electrical Characteristics" provides conditions for actual device operation.

Note 2: $V_{SS} = 0V$ unless otherwise specified.

Note 3: I_{OH} and I_{OL} are tested one output at a time.

DC Electrical Characteristics CD4029BC (Note 2) (Continued)

| Symbol | Parameter | Conditions | -40°C | | +25°C | | | +85°C | | Units |
|-----------------|------------------------------------|-------------------------------------------------------|-------|------|-------|-------------------|------|-------|------|-------|
| | | | Min | Max | Min | Typ | Max | Min | Max | |
| V _{IL} | Low Level Input Voltage | V _{DD} = 5V, V _O = 0.5V or 4.5V | | 1.5 | | | | 1.5 | | V |
| | | V _{DD} = 10V, V _O = 1V or 9V | | 3.0 | | | | 3.0 | | V |
| | | V _{DD} = 15V, V _O = 1.5V or 13.5V | | 4.0 | | | | 4.0 | | V |
| V _{IH} | High Level Input Voltage | V _{DD} = 5V, V _O = 0.5V or 4.5V | 3.5 | | 3.5 | | | 3.5 | | V |
| | | V _{DD} = 10V, V _O = 1V or 9V | 7.0 | | 7.0 | | | 7.0 | | V |
| | | V _{DD} = 15V, V _O = 1.5V or 13.5V | 11.0 | | 11.0 | | | 11.0 | | V |
| I _{OL} | Low Level Output Current (Note 3) | V _{DD} = 5V, V _O = 0.4V | 0.52 | | 0.44 | 0.88 | | 0.36 | | mA |
| | | V _{DD} = 10V, V _O = 0.5V | 1.3 | | 1.1 | 2.25 | | 0.9 | | mA |
| | | V _{DD} = 15V, V _O = 1.5V | 3.6 | | 3.0 | 8.8 | | 2.4 | | mA |
| I _{OH} | High Level Output Current (Note 3) | V _{DD} = 5V, V _O = 4.6V | -0.52 | | -0.44 | -0.88 | | -0.36 | | mA |
| | | V _{DD} = 10V, V _O = 9.5V | -1.3 | | -1.1 | -2.25 | | -0.9 | | mA |
| | | V _{DD} = 15V, V _O = 13.5V | -3.6 | | -3.0 | -8.8 | | -2.4 | | mA |
| I _{IN} | Input Current | V _{DD} = 15V, V _{IN} = 0V | | -0.3 | | -10 ⁻⁵ | -0.3 | | -1.0 | μA |
| | | V _{DD} = 15V, V _{IN} = 15V | | 0.3 | | 10 ⁻⁵ | 0.3 | | 1.0 | μA |

AC Electrical Characteristics*

T_A = 25°C, C_L = 50 pF, R_L = 200k, Input t_{rCL} = t_{fCL} = 20 ns, unless otherwise specified

| Symbol | Parameter | Conditions | Min | Typ | Max | Units |
|--------------------------------------|----------------------------------------|------------------------|-----|-----|-----|-------|
| CLOCKED OPERATION | | | | | | |
| t _{PHL} or t _{PLH} | Propagation Delay Time to Q Outputs | V _{DD} = 5V | | 200 | 400 | ns |
| | | V _{DD} = 10V | | 85 | 170 | ns |
| | | V _{DD} = 15V | | 70 | 140 | ns |
| t _{PHL} or t _{PLH} | Propagation Delay Time to Carry Output | V _{DD} = 5V | | 320 | 640 | ns |
| | | V _{DD} = 10V | | 135 | 270 | ns |
| | | V _{DD} = 15V | | 110 | 220 | ns |
| t _{PHL} or t _{PLH} | Propagation Delay Time to Carry Output | C _L = 15 pF | | | | |
| | | V _{DD} = 5V | | 285 | 570 | ns |
| | | V _{DD} = 10V | | 120 | 240 | ns |
| | | V _{DD} = 15V | | 95 | 190 | ns |
| t _{THL} or t _{TLH} | Transition Time/Q or Carry Output | V _{DD} = 5V | | 100 | 200 | ns |
| | | V _{DD} = 10V | | 50 | 100 | ns |
| | | V _{DD} = 15V | | 40 | 80 | ns |
| t _{WH} or t _{WL} | Minimum Clock Pulse Width | V _{DD} = 5V | | 160 | 320 | ns |
| | | V _{DD} = 10V | | 70 | 135 | ns |
| | | V _{DD} = 15V | | 55 | 110 | ns |
| t _{rCL} or t _{fCL} | Maximum Clock Rise and Fall Time | V _{DD} = 5V | 15 | | | μs |
| | | V _{DD} = 10V | 10 | | | μs |
| | | V _{DD} = 15V | 5 | | | μs |
| t _{SU} | Minimum Set-Up Time | V _{DD} = 5V | | 180 | 360 | ns |
| | | V _{DD} = 10V | | 70 | 140 | ns |
| | | V _{DD} = 15V | | 55 | 110 | ns |
| f _{CL} | Maximum Clock Frequency | V _{DD} = 5V | 1.5 | 3.1 | | MHz |
| | | V _{DD} = 10V | 3.7 | 7.4 | | MHz |
| | | V _{DD} = 15V | 4.5 | 9 | | MHz |
| C _{IN} | Average Input Capacitance | Any Input | | 5 | 7.5 | pF |
| C _{PD} | Power Dissipation Capacitance | Per Package (Note 4) | | 65 | | pF |

Note 1: "Absolute Maximum Ratings" are those values beyond which the safety of the device cannot be guaranteed. Except for "Operating Temperature Range" they are not meant to imply that the devices should be operated at these limits. The table of "Electrical Characteristics" provides conditions for actual device operation.

Note 2: V_{SS} = 0V unless otherwise specified.

Note 3: I_{OH} and I_{OL} are tested one output at a time.

AC Electrical Characteristics*

$T_A = 25^\circ\text{C}$, $C_L = 50\text{ pF}$, $R_L = 200\text{ k}$, Input $t_{rCL} = t_{fCL} = 20\text{ ns}$, unless otherwise specified (Continued)

| Symbol | Parameter | Conditions | Min | Typ | Max | Units |
|--------------------------------|----------------------------------------|-----------------------|-----|-----|-----|-------|
| PRESET ENABLE OPERATION | | | | | | |
| t_{PHL} or t_{PLH} | Propagation Delay Time to Q output | $V_{DD} = 5\text{V}$ | | 285 | 570 | ns |
| | | $V_{DD} = 10\text{V}$ | | 115 | 230 | ns |
| | | $V_{DD} = 15\text{V}$ | | 95 | 195 | ns |
| t_{PHL} or t_{PLH} | Propagation Delay Time to Carry Output | $V_{DD} = 5\text{V}$ | | 400 | 800 | ns |
| | | $V_{DD} = 10\text{V}$ | | 165 | 330 | ns |
| | | $V_{DD} = 15\text{V}$ | | 135 | 260 | ns |
| t_{WH} | Minimum Preset Enable Pulse Width | $V_{DD} = 5\text{V}$ | | 80 | 160 | ns |
| | | $V_{DD} = 10\text{V}$ | | 30 | 60 | ns |
| | | $V_{DD} = 15\text{V}$ | | 25 | 50 | ns |
| t_{REM} | Minimum Preset Enable Removal Time | $V_{DD} = 5\text{V}$ | | 150 | 300 | ns |
| | | $V_{DD} = 10\text{V}$ | | 60 | 120 | ns |
| | | $V_{DD} = 15\text{V}$ | | 50 | 100 | ns |
| CARRY INPUT OPERATION | | | | | | |
| t_{PHL} or t_{PLH} | Propagation Delay Time to Carry Output | $V_{DD} = 5\text{V}$ | | 265 | 530 | ns |
| | | $V_{DD} = 10\text{V}$ | | 110 | 220 | ns |
| | | $V_{DD} = 15\text{V}$ | | 90 | 180 | ns |
| t_{PHL} , t_{PLH} | Propagation Delay Time to Carry Output | $C_L = 15\text{ pF}$ | | | | |
| | | $V_{DD} = 5\text{V}$ | | 200 | 400 | ns |
| | | $V_{DD} = 10\text{V}$ | | 85 | 170 | ns |
| | | $V_{DD} = 15\text{V}$ | | 70 | 140 | ns |

*AC Parameters are guaranteed by DC correlated testing.


Note 1: "Absolute Maximum Ratings" are those values beyond which the safety of the device cannot be guaranteed. Except for "Operating Temperature Range" they are not meant to imply that the devices should be operated at these limits. The table of "Electrical Characteristics" provides conditions for actual device operation.

Note 2: $V_{SS} = 0\text{V}$ unless otherwise specified.

Note 3: I_{OH} and I_{OL} are tested one output at a time.

Note 4: C_{pD} determines the no load AC power consumption of any CMOS device. For complete explanation, see 54C/74C Family Characteristics application note, AN-90.


Connection Diagram



Order Number CD4029B


Logic Waveforms

Decade Mode




TL/F/5960-3

Binary Mode



TL/F/5960-4


Switching Time Waveforms



TL/F/5960-5


Cascading Packages

Parallel Clocking



TL/F/5960-6


Ripple Clocking




TL/F/5960-7

Carry out lines at the 2nd or later stages may have a negative-going spike due to differential internal delays. These spikes do not affect counter operation, but if the carry out is used to trigger external circuitry the carry out should be gated with the clock.

Physical Dimensions inches (millimeters)



Order Number CD4029BMJ or CD4029BCJ
NS Package Number J16A



Order Number CD4029BMN or CD4029BCN
NS Package Number N16E

LIFE SUPPORT POLICY

NATIONAL'S PRODUCTS ARE NOT AUTHORIZED FOR USE AS CRITICAL COMPONENTS IN LIFE SUPPORT DEVICES OR SYSTEMS WITHOUT THE EXPRESS WRITTEN APPROVAL OF THE PRESIDENT OF NATIONAL SEMICONDUCTOR CORPORATION. As used herein:

1. Life support devices or systems are devices or systems which, (a) are intended for surgical implant into the body, or (b) support or sustain life, and whose failure to perform, when properly used in accordance with instructions for use provided in the labeling, can be reasonably expected to result in a significant injury to the user.
2. A critical component is any component of a life support device or system whose failure to perform can be reasonably expected to cause the failure of the life support device or system, or to affect its safety or effectiveness.



National Semiconductor Corporation
1111 West Bardin Road
Arlington, TX 76017
Tel: 1(800) 272-9959
Fax: 1(800) 737-7018

National Semiconductor Europe
Fax: (+49) 0-180-530 85 86
Email: cnjwge@tevm2.nsc.com
Deutsch Tel: (+49) 0-180-530 85 85
English Tel: (+49) 0-180-532 78 32
Français Tel: (+49) 0-180-532 93 58
Italiano Tel: (+49) 0-180-534 16 80

National Semiconductor Hong Kong Ltd.
19th Floor, Straight Block,
Ocean Centre, 5 Canton Rd.
Tsimshatsui, Kowloon
Hong Kong
Tel: (852) 2737-1600
Fax: (852) 2736-9960

National Semiconductor Japan Ltd.
Tel: 81-043-299-2309
Fax: 81-043-299-2408

National does not assume any responsibility for use of any circuitry described, no circuit patent licenses are implied and National reserves the right at any time without notice to change said circuitry and specifications.